

BF4/5/6

TECHNICAL SPECIFICATIONS



	BF6 NEW	BF5 NEW	BF4 NEW
TYPE	four-stroke OHV one cylinder / two valves	four-stroke OHV one cylinder / two valves	four-stroke OHV one cylinder / two valves
DISPLACEMENT	127	127	127
BORE & STROKE	60 x 45	60 x 45	60 x 45
FULL THROTTLE RPM RANGE	5.000-6.000 RPM	4.500-5.500 RPM	4.500-5.500 RPM
RATED POWER	6HP @ 6000 RPM (4.4KW)	5HP @ 5500 RPM (3.7KW)	4HP @ 5500 RPM (3.7KW)
COOLING SYSTEM	Water Cooled	Water Cooled	Water Cooled
INDUCTION	One Carburettor	One Carburettor	One Carburettor
IGNITION SYSTEM	Digital CDI	Digital CDI	Digital CDI
STARTING SYSTEM	Recoil	Recoil	Recoil
EXHAUST	Under Water Above Propeller	Under Water Above Propeller	Under Water Above Propeller
DRIVE			
GEAR RATIO	2.08.1	2.08.1	2.08.1
GEAR SHIFT	F-N-R	F-N-R	F-N-R
EQUIPMENT			
ALTERNATOR OUTPUT	-	-	-
PROPELLER	5 models available	5 models available	5 models available
DIAMETER X PITCH (S-TYPE)	7 7/8 x 7 1/2 Inches	7 7/8 x 7 1/2 Inches	7 7/8 x 7 1/2 Inches
(L-TYPE)	7 7/8 x 7 1/2 Inches	7 7/8 x 7 1/2 Inches	7 7/8 x 7 1/2 Inches
(X-TYPE)	-	-	-
POWER TRIM & TILT	Mechanical Tilt	Mechanical Tilt	Mechanical Tilt
GAS-ASSISTED TILT	-	-	-
EMERGENCY STOP SWITCH	Standard	Standard	Standard
OIL PRESSURE ALERT	Standard	Standard	Standard
TEMPERATURE ALERT	-	-	-
REV-LIMITER	Standard	Standard	Standard
SPEEDOMETER PICKUP	-	-	-
DIMENSIONS			
OVERALL LENGTH	524mm	524mm	524mm
OVERALL WIDTH	347mm	347mm	347mm
OVERALL HEIGHT (S-TYPE)	1020mm	1020mm	1020mm
(L-TYPE)	1147mm	1147mm	1147mm
(X-TYPE)	-	-	-
(XXL-TYPE)	-	-	-
TRANSOM HEIGHT (S-TYPE)	434mm	434mm	434mm
(L-TYPE)	561mm	561mm	561mm
(X-TYPE)†	-	-	-
(XXL-TYPE)†	-	-	-
DRY WEIGHT (KG)	27	27	27

UNMATCHED RELIABILITY

1300 1 HONDA | marine.honda.com.au



HONDA
MARINE